

L | SERIES

HINO L6 LoPro 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE	
Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	240 hp @ 2,300 rpm
Max. Torque (SAE Gross)	560 lbs.-ft. @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE		
GVWR, kg (lbs.)		11,570 (25,500)
GCWR, kg (lbs.)		11,793 (26,000)
Maximum Speed, km/hr		104
Gradeability (tan θ) %		31.8
Rear Axle Ratio		4.11
Transmission	Model	Allison 2200 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.102
	2nd	1.811
	3rd	1.406
	4th	1.000
	5th	0.712
	6th	0.614
	Rev.	4.492

WEIGHT CAPACITIES, kg (lbs.)	
GAWR - Front Axle	3,630 (8,000)
GAWR - Rear Axle	7,940 (17,500)

AXLE / SUSPENSION	
Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS	
Air conditioning	
Tilt & telescopic steering column with lock	
Steering wheel, 4 spoke, black with control switches	
Power windows and door locks with keyless entry	
Power and heated outer rearview mirrors	
Convex mirror (2)	
Driver's seat - high-back seat with air suspension & arm rest	
Passenger seat - 2-person high-back bench seat	
Cruise control	
1000W/120V engine block heater	
LED low & high beam	

FRAME	
Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	56.2 (80,000)
Resisting Bending Moment, one side kgf-mm (in.-lbs.)	1,188,862 (1,031,900)
Tow hook	One, front right side

CHASSIS EQUIPMENT	
Fuel Tank ltr. (US gallon)	189 (50) mounted under cab, left side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank ltr. (US gallon)	28 (7.0)

WHEELS / TIRES	
Wheels	19.5 x 6.75, 8-stud disc
Tires	Bridgestone 245/70R19.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT	
Batteries	Two 12V, parallel connection, 1300 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES	
Service Brake	Hydraulic, 4-wheel disc with ABS
Parking Brake	Mechanical, internal expanding acting on differential

OPTIONAL EQUIPMENT	
Hendrickson rear air suspension	
Alcoa aluminum wheels	
Multimedia audio system with Bluetooth® and Navigation	
Batteries (see Dealer for available options)	
Orange safety belts, driver & passenger	
4" front bumper extension	
One piece, chrome bumper	
Cab paint, exterior (see Dealer for available colours)	
Fender mirrors	

HINOWATCH	
No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).	

DIMENSIONS mm (in)	L6L-175	L6L-187	L6L-205	L6L-217	L6L-235	L6L-253	L6L-271
Wheelbase	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Cab to axle	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Overall length	7,493 (295.0)	7,798 (307.0)	8,255 (325.0)	8,560 (337.0)	9,474 (373.0)	9,931 (391.0)	10,389 (409.0)
Overall height	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
Overall width	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)
Frame height at rear axle	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Rear overhang	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)
Turning radius - tire	7,320 (288.2)	7,760 (305.5)	8,430 (331.9)	8,880 (349.6)	9,550 (376.0)	10,220 (402.4)	10,900 (429.1)
Turning radius - swept	7,830 (308.3)	8,270 (325.6)	8,940 (352.0)	9,390 (369.7)	10,060 (396.1)	10,730 (422.4)	11,410 (449.2)
CHASSIS WEIGHT	L6L-175	L6L-187	L6L-205	L6L-217	L6L-235	L6L-253	L6L-271
Front axle kgs (lbs.)	2,765 (6,095)	2,785 (6,140)	2,830 (6,240)	2,840 (6,260)	2,870 (6,325)	2,895 (6,380)	2,900 (6,395)
Rear axle kgs (lbs.)	1,505 (3,315)	1,510 (3,330)	1,515 (3,340)	1,555 (3,430)	1,545 (3,405)	1,535 (3,385)	1,560 (3,440)
Total weight kgs (lbs.)	4,270 (9,410)	4,295 (9,470)	4,345 (9,580)	4,395 (9,690)	4,415 (9,730)	4,430 (9,765)	4,460 (9,835)

NOTE :
DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.



L | SERIES

HINO L6 LoPro Air Brake Air Suspension 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE	
Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	240 hp @ 2,300 rpm
Max. Torque (SAE Gross)	560 lbs.-ft. @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE		
GVWR, kg (lbs.)		11,570 (25,500)
GCWR, kg (lbs.)		11,793 (26,000)
Maximum Speed, km/hr		104
Gradeability (tan θ) %		31.8
Rear Axle Ratio		4.11
Transmission	Model	Allison 2200 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.102
	2nd	1.811
	3rd	1.406
	4th	1.000
	5th	0.712
	6th	0.614
	Rev.	4.492

WEIGHT CAPACITIES, kg (lbs.)	
GAWR - Front Axle	3,630 (8,000)
GAWR - Rear Axle	7,940 (17,500)

AXLE / SUSPENSION	
Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS	
Air conditioning	
Tilt & telescopic steering column with lock	
Steering wheel, 4 spoke, black with control switches	
Power windows and door locks with keyless entry	
Power and heated outer rearview mirrors	
Convex mirror (2)	
Driver's seat - high-back seat with air suspension & arm rest	
Passenger seat - 2-person high-back bench seat	
Cruise control	
1000W/120V engine block heater	
LED low & high beam	
Air Suspension, Hendrickson with dump valve	

FRAME	
Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	56.2 (80,000)
Resisting Bending Moment, one side kgf-mm (in-lbs.)	1,188,862 (1,031,900)
Tow hook	One, front right side

CHASSIS EQUIPMENT	
Fuel Tank ltr. (US gallon)	189 (50) mounted under cab, left side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank ltr. (US gallon)	28 (7.0)

WHEELS / TIRES	
Wheels	19.5 x 7.50, 10-stud disc
Tires	Bridgestone 245/70R19.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT	
Batteries	Two 12V, parallel connection, 1300 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES	
Service Brake	Full air, dual circuit, 4-wheel drum with ABS
Parking Brake	Spring brake acting on rear wheels

OPTIONAL EQUIPMENT	
Alcoa aluminum wheels	
Multimedia audio system with Bluetooth® and Navigation	
Batteries (see Dealer for available options)	
Orange safety belts, driver & passenger	
4" front bumper extension	
One piece, chrome bumper	
Cab paint, exterior (see Dealer for available colours)	
Fender Mirrors	

HINOWATCH	
No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).	

DIMENSIONS mm (in)	L6LAB-175	L6LAB-187	L6LAB-205	L6LAB-217	L6LAB-235	L6LAB-253	L6LAB-271
Wheelbase	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Cab to axle	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Overall length	7,493 (295.0)	7,798 (307.0)	8,255 (325.0)	8,560 (337.0)	9,474 (373.0)	9,931 (391.0)	10,389 (409.0)
Overall height	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
Overall width	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)	2,470 (97.2)
Frame height at rear axle	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Rear overhang	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)
Turning radius - tire	7,250 (285.4)	7,690 (302.8)	8,360 (329.1)	8,800 (346.5)	9,470 (372.8)	10,130 (398.8)	10,800 (425.2)
Turning radius - swept	7,765 (305.7)	8,205 (323.0)	8,875 (349.4)	9,315 (366.7)	9,985 (393.1)	10,645 (419.1)	11,315 (445.5)
CHASSIS WEIGHT	L6LAB-175	L6LAB-187	L6LAB-205	L6LAB-217	L6LAB-235	L6LAB-253	L6LAB-271
Front axle kgs (lbs.)	2,830 (6,240)	2,855 (6,295)	2,900 (6,395)	2,910 (6,415)	2,945 (6,490)	2,965 (6,535)	2,970 (6,545)
Rear axle kgs (lbs.)	1,625 (3,580)	1,630 (3,595)	1,630 (3,595)	1,670 (3,680)	1,655 (3,650)	1,650 (3,635)	1,675 (3,690)
Total weight kgs (lbs.)	4,455 (9,820)	4,485 (9,890)	4,530 (9,990)	4,580 (10,095)	4,600 (10,140)	4,615 (10,170)	4,645 (10,235)

NOTE :
DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.



L | SERIES

HINO L6 LoPro High Horsepower 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE	
Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	260 hp @ 2,300 rpm
Max. Torque (SAE Gross)	660 lbs.-ft @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE		
GVWR, kg (lbs.)		11,570 (25,500)
GCWR, kg (lbs.)		11,793 (26,000)
Maximum Speed, km/hr		104
Gradeability (tan θ) %		42
Rear Axle Ratio		4.11
Transmission	Model	Allison 2200 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.102
	2nd	1.811
	3rd	1.406
	4th	1.000
	5th	0.712
	6th	0.614
	Rev.	4.492

WEIGHT CAPACITIES, kg (lbs.)	
GAWR - Front Axle	3,630 (8,000)
GAWR - Rear Axle	7,940 (17,500)

AXLE / SUSPENSION	
Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS	
Air conditioning	
Tilt & telescopic steering column with lock	
Steering wheel, 4 spoke, black with control switches	
Power windows and door locks with keyless entry	
Power and heated outer rearview mirrors	
Convex mirror (2)	
Driver's seat - high-back seat with air suspension & arm rest	
Passenger seat - 2-person high-back bench seat	
Cruise control	
1000W/120V engine block heater	
LED low & high beam	

DIMENSIONS mm (in)	L6LU-217
Wheelbase	5,512 (217.0)
Cab to axle	3,800 (149.6)
Overall length	8,560 (337.0)
Overall height	2,615 (103.0)
Overall width	2,470 (97.2)
Frame height at rear axle	900 (35.4)
Rear overhang	2,007 (79.0)
Turning radius - tire	8,880 (349.6)
Turning radius - swept	9,390 (369.7)
CHASSIS WEIGHT	L6LU-217
Front axle kgs (lbs.)	2,855 (6,295)
Rear axle kgs (lbs.)	1,570 (3,460)
Total weight kgs (lbs.)	4,425 (9,755)

NOTE :
DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.

FRAME	
Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	56.2 (80,000)
Resisting Bending Moment, one side kgf-mm (in.-lbs.)	1,188,862 (1,031,900)
Tow hook	Front, dual tow hooks

CHASSIS EQUIPMENT	
Fuel Tank ltr. (US gallon)	189 (50) mounted under cab, left side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank ltr. (US gallon)	28 (7.0)

WHEELS / TIRES	
Wheels	19.5 x 6.75, 8-stud disc
Tires	Bridgestone 245/70R19.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT	
Batteries	Three 12V, parallel connection, 1950 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES	
Service Brake	Hydraulic, 4-wheel disc with ABS
Parking Brake	Mechanical, internal expanding acting on differential

OPTIONAL EQUIPMENT	
Hendrickson rear air suspension	
Alcoa aluminum wheels	
Multimedia audio system with Bluetooth® and Navigation	
Batteries (see Dealer for available options)	
Orange safety belts, driver & passenger	
4" front bumper extension	
One piece, chrome bumper	
Cab paint, exterior (see Dealer for available colours)	
Fender Mirrors	

HINOWATCH	
No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).	



L | SERIES

HINO L6 LoPro High Horsepower Air Brake Air Suspension 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE	
Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	260 hp @ 2,300 rpm
Max. Torque (SAE Gross)	660 lbs.-ft @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE		
GVWR, kg (lbs.)	11,570 (25,500)	
GCWR, kg (lbs.)	11,793 (26,000)	
Maximum Speed, km/hr	104	
Gradeability (tan θ) %	42	
Rear Axle Ratio	4.11	
Transmission	Model	Allison 2200 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.102
	2nd	1.811
	3rd	1.406
	4th	1.000
	5th	0.712
	6th	0.614
	Rev.	4.492

WEIGHT CAPACITIES, kg (lbs.)	
GAWR - Front Axle	3,630 (8,000)
GAWR - Rear Axle	7,940 (17,500)

AXLE / SUSPENSION	
Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS	
Air conditioning	
Tilt & telescopic steering column with lock	
Steering wheel, 4 spoke, black with control switches	
Power windows and door locks with keyless entry	
Power and heated outer rearview mirrors	
Convex mirror (2)	
Driver's seat - high-back seat with air suspension & arm rest	
Passenger seat - 2-person high-back bench seat	
Cruise control	
1000W/120V engine block heater	
LED low & high beam	
Air Suspension, Hendrickson with dump valve	

FRAME	
Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	56.2 (80,000)
Resisting Bending Moment, one side kgf-mm (in-lbs.)	1,188,862 (1,031,900)
Tow hook	Front, dual tow hooks

CHASSIS EQUIPMENT	
Fuel Tank ltr. (US gallon)	189 (50) mounted under cab, left side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank ltr. (US gallon)	28 (7.0)

WHEELS / TIRES	
Wheels	19.5 x 7.50, 10-stud disc
Tires	Bridgestone 245/70R19.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT	
Batteries	Two, 12V parallel connection, 1950 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES	
Service Brake	Full air, dual circuit, 4-wheel drum with ABS
Parking Brake	Spring brake acting on rear wheels

OPTIONAL EQUIPMENT	
Alcoa aluminum wheels	
Multimedia audio system with Bluetooth® and Navigation	
Batteries (see Dealer for available options)	
Orange safety belts, driver & passenger	
4" front bumper extension	
One piece, chrome bumper	
Cab paint, exterior (see Dealer for available colours)	
Fender mirrors	

HINOWATCH	
No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).	

DIMENSIONS mm (in)	L6LUAB-217
Wheelbase	5,512 (217.0)
Cab to axle	3,800 (149.6)
Overall length	8,560 (337.0)
Overall height	2,615 (103.0)
Overall width	2,470 (97.2)
Frame height at rear axle	900 (35.4)
Rear overhang	2,007 (79.0)
Turning radius - tire	8,800 (346.5)
Turning radius - swept	9,315 (366.7)
CHASSIS WEIGHT	L6LUAB-217
Front axle kgs (lbs.)	2,925 (6,450)
Rear axle kgs (lbs.)	1,685 (3,715)
Total weight kgs (lbs.)	4,610 (10,165)

NOTE :
DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.



L | SERIES

HINO L6 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE

Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	240 hp @ 2,300 rpm
Max. Torque (SAE Gross)	560 lbs.-ft. @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE

GVWR, kg (lbs.)	11,771 (25,950)	
GCWR, kg (lbs.)	11,793 (26,000)	
Maximum Speed, km/hr	104	
Gradeability (tan θ) %	34.3	
Rear Axle Ratio	5.57	
Transmission	Model	Allison 2200 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.102
	2nd	1.811
	3rd	1.406
	4th	1.000
	5th	0.712
	6th	0.614
Rev.	4.492	

WEIGHT CAPACITIES, kg (lbs.)

GAWR - Front Axle	4,540 (10,000)
GAWR - Rear Axle	8,620 (19,000)

AXLE / SUSPENSION

Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS

Air conditioning
Tilt & telescopic steering column with lock
Steering wheel, 4 spoke, black with control switches
Power windows and door locks with keyless entry
Power and heated outer rearview mirrors
Convex mirror (2)
Driver's seat - high-back seat with air suspension & arm rest
Passenger seat - 2-person high-back bench seat
Cruise control
1000W/120V engine block heater
LED low and high beam

FRAME

Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	56.2 (80,000)
Resisting Bending Moment, one side kgf-mm (in-lbs.)	1,188,862 (1,031,900)
Tow hook	One, front right side

CHASSIS EQUIPMENT

Fuel Tank Itr. (US gallon)	189 (50) mounted under cab, left side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank Itr. (US gallon)	28 (7.0)

WHEELS / TIRES

Wheels	22.5 x 8.25, 10-stud disc
Tires	Bridgestone 11R22.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT

Batteries	Two 12V, parallel connection, 1300 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES

Service Brake	Hydraulic, 4-wheel disc with ABS
Parking Brake	Mechanical, internal expanding acting on differential

OPTIONAL EQUIPMENT

Hendrickson rear air suspension
Alcoa aluminum wheels
Multimedia audio system with Bluetooth® and Navigation
Batteries (see Dealer for available options)
90-gallon aluminum fuel tank, left side mounted
Orange safety belts, driver & passenger
4" front bumper extension
One piece, chrome bumper
Cab paint, exterior (see Dealer for available colours)
Fender mirrors

HINOWATCH

No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).

DIMENSIONS mm (in)	L6-175	L6-187	L6-205	L6-217	L6-235	L6-253	L6-271
Wheelbase	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Cab to axle	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Overall length	7,493 (295.0)	7,798 (307.0)	8,255 (325.0)	8,560 (337.0)	9,474 (373.0)	9,931 (391.0)	10,389 (409.0)
Overall height	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
Overall width	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Frame height at rear axle	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Rear overhang	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)
Turning radius - tire	7,240 (285.0)	7,680 (302.4)	8,340 (328.3)	8,790 (346.1)	9,450 (372.0)	10,120 (398.4)	10,780 (424.4)
Turning radius - swept	7,770 (305.9)	8,210 (323.2)	8,870 (349.2)	9,320 (366.9)	9,980 (392.9)	10,650 (419.3)	11,310 (445.3)
CHASSIS WEIGHT	L6-175	L6-187	L6-205	L6-217	L6-235	L6-253	L6-271
Front axle kgs (lbs.)	2,865 (6,315)	2,890 (6,370)	2,940 (6,480)	2,945 (6,495)	2,995 (6,605)	3,020 (6,660)	3,065 (6,760)
Rear axle kgs (lbs.)	1,595 (3,515)	1,585 (3,495)	1,615 (3,560)	1,655 (3,650)	1,645 (3,625)	1,635 (3,605)	1,660 (3,660)
Total weight kgs (lbs.)	4,460 (9,830)	4,475 (9,865)	4,525 (9,975)	4,540 (10,010)	4,565 (10,065)	4,585 (10,110)	4,640 (10,230)

NOTE :

DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.



L | SERIES

HINO L7 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE	
Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	260 hp @ 2,300 rpm
Max. Torque (SAE Gross)	660 lbs.-ft @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE		
GVWR, kg (lbs.)	14,950 (33,000)	
GCWR, kg (lbs.)	14,950 (33,000)	
Maximum Speed, km/hr	104	
Gradeability (tan θ) %	39.5	
Rear Axle Ratio	5.57	
Transmission	Model	Allison 2500 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.512
	2nd	1.896
	3rd	1.439
	4th	1.000
	5th	0.737
	6th	0.643
Rev.	5.086	

WEIGHT CAPACITIES, kg (lbs.)	
GAWR - Front Axle	5,440 (12,000)
GAWR - Rear Axle	9,530 (21,000)

AXLE / SUSPENSION	
Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS	
Air conditioning	
Tilt & telescopic steering column with lock	
Steering wheel, 4 spoke, black with control switches	
Power windows and door locks with keyless entry	
Power and heated outer rearview mirrors	
Convex mirror (2)	
Driver's seat - high-back seat with air suspension & arm rest	
Passenger seat - 2-person high-back bench seat	
Cruise control	
1000W/120V engine block heater	
LED low & high beam	

FRAME	
Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	56.2 (80,000)
Resisting Bending Moment, one side kgf-mm (in-lbs.)	1,475,588 (1,280,800)
Tow hook	One, front right side

CHASSIS EQUIPMENT	
Fuel Tank ltr. (US gallon)	189 (50) mounted under cab, left side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank ltr. (US gallon)	28 (7.0)

WHEELS / TIRES	
Wheels	22.5 x 8.25, 10-stud disc
Tires	Bridgestone 11R22.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT	
Batteries	Two 12V, parallel connection, 1300 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES	
Service Brake	Hydraulic, 4-wheel disc with ABS
Parking Brake	Mechanical, internal expanding acting on differential

OPTIONAL EQUIPMENT	
Hendrickson rear air suspension	
Alcoa aluminum wheels	
90-gallon aluminum fuel tank, driver's side mounted	
Multimedia audio system with Bluetooth® and Navigation	
One piece, chrome bumper	
4" front bumper extension	
Cab paint, exterior (see Dealer for available colours)	
Batteries (see Dealer for available options)	
Orange safety belts, driver & passenger	
Fender mirrors	

HINOWATCH	
No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).	

DIMENSIONS mm (in)	L7-187	L7-205	L7-217	L7-235	L7-253	L7-271
Wheelbase	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Cab to axle	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Overall length	7,798 (307.0)	8,255 (325.0)	8,560 (337.0)	9,474 (373.0)	9,931 (391.0)	10,389 (409.0)
Overall height	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
Overall width	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)
Frame height at rear axle	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Rear overhang	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)
Turning radius - tire	7,680 (302.4)	8,340 (328.3)	8,790 (346.1)	9,450 (372.0)	10,120 (398.4)	10,780 (424.4)
Turning radius - swept	8,210 (323.2)	8,870 (349.2)	9,320 (366.9)	9,980 (392.9)	10,650 (419.3)	11,310 (445.3)
CHASSIS WEIGHT	L7-187	L7-205	L7-217	L7-235	L7-253	L7-271
Front axle kgs (lbs.)	2,935 (6,470)	2,990 (6,590)	2,995 (6,605)	3,050 (6,725)	3,080 (6,790)	3,125 (6,890)
Rear axle kgs (lbs.)	1,650 (3,640)	1,655 (3,650)	1,670 (3,680)	1,645 (3,625)	1,645 (3,625)	1,660 (3,660)
Total weight kgs (lbs.)	4,585 (10,110)	4,645 (10,240)	4,665 (10,285)	4,695 (10,350)	4,725 (10,415)	4,785 (10,550)

NOTE :
DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.



L | SERIES

HINO L7 Air Brake Air Suspension 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE	
Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	260 hp @ 2,300 rpm
Max. Torque (SAE Gross)	660 lbs.-ft @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE		
GVWR, kg (lbs.)		14,950 (33,000)
GCWR, kg (lbs.)		14,950 (33,000)
Maximum Speed, km/hr		104
Gradeability (tan θ) %		39.5
Rear Axle Ratio		5.57
Transmission	Model	Allison 2500 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.512
	2nd	1.896
	3rd	1.439
	4th	1.000
	5th	0.737
	6th	0.643
	Rev.	5.086

WEIGHT CAPACITIES, kg (lbs.)	
GAWR - Front Axle	5,440 (12,000)
GAWR - Rear Axle	9,530 (21,000)

AXLE / SUSPENSION	
Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS	
Air conditioning	
Tilt & telescopic steering column with lock	
Steering wheel, 4 spoke, black with control switches	
Power windows and door locks with keyless entry	
Power and heated outer rearview mirrors	
Convex mirror (2)	
Driver's seat - high-back seat with air suspension & arm rest	
Passenger seat - 2-person high-back bench seat	
Cruise control	
1000W/120V engine block heater	
LED low & high beam	
Air horn	
Air Suspension, Hendrickson with dump valve	

FRAME	
Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	56.2 (80,000)
Resisting Bending Moment, one side kgf-mm (in-lbs.)	1,475,588 (1,280,800)
Tow hook	One, front right side

CHASSIS EQUIPMENT	
Fuel Tank ltr. (US gallon)	189 (50) mounted under cab, left side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank ltr. (US gallon)	28 (7.0)

WHEELS / TIRES	
Wheels	22.5 x 8.25, 10-stud disc
Tires	Bridgestone 11R22.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT	
Batteries	Two 12V, parallel connection, 1300 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES	
Service Brake	Full air, dual circuit, 4-wheel drum with ABS
Parking Brake	Spring brake acting on rear wheels

OPTIONAL EQUIPMENT	
Rear differential lock, driver control	
Alcoa aluminum wheel	
Multimedia audio system with Bluetooth® and Navigation	
90-gallon driver's side fuel tank	
One piece, chrome bumper	
4" front bumper extension	
Cab paint, exterior (see Dealer for available colours)	
Batteries (see Dealer for available options)	
Orange safety belts, driver & passenger	
Fender mirrors	

HINOWATCH	
No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).	

DIMENSIONS mm (in)	L7AB-187	L7AB-205	L7AB-217	L7AB-235	L7AB-253	L7AB-271
Wheelbase	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Cab to axle	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Overall length	7,798 (307.0)	8,255 (325.0)	8,560 (337.0)	9,474 (373.0)	9,931 (391.0)	10,389 (409.0)
Overall height	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
Overall width	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)
Frame height at rear axle	995 (39.2)	995 (39.2)	995 (39.2)	995 (39.2)	995 (39.2)	995 (39.2)
Rear overhang	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)
Turning radius - tire	7,690 (302.8)	8,350 (328.7)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius - swept	8,210 (323.2)	8,870 (349.2)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
CHASSIS WEIGHT	L7AB-187	L7AB-205	L7AB-217	L7AB-235	L7AB-253	L7AB-271
Front axle kgs (lbs.)	2,940 (6,480)	2,990 (6,590)	3,000 (6,615)	3,050 (6,720)	3,080 (6,790)	3,125 (6,890)
Rear axle kgs (lbs.)	1,650 (3,640)	1,660 (3,660)	1,670 (3,680)	1,650 (3,640)	1,650 (3,640)	1,665 (3,670)
Total weight kgs (lbs.)	4,590 (10,120)	4,650 (10,250)	4,670 (10,295)	4,700 (10,360)	4,730 (10,430)	4,790 (10,560)

NOTE :
 DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.



L | SERIES

HINO L8 Air Brake Air Suspension 2022

ALL 2022 MODELS REQUIRE ULTRA-LOW SULFUR DIESEL FUEL

ENGINE	
Model	Cummins B6.7
Displacement	6.7L
Type	6-cyl, in-line, water cooled
Max. Output (SAE Gross)	260 hp @ 2,300 rpm
Max. Torque (SAE Gross)	660 lbs.-ft @ 1,600 rpm
Fuel System	High Pressure Common Rail System

POWERTRAIN & PERFORMANCE		
GVWR, kg (lbs.)	15,870 (35,000)	
GCWR, kg (lbs.)	24,947 (55,000)	
Maximum Speed, km/hr	104	
Gradeability (tan θ) %	54	
Rear Axle Ratio	5.63	
Transmission	Model	Allison 3000 RDS (PTO capable)
	Type	6-speed automatic
Ratio	1st	3.487
	2nd	1.864
	3rd	1.409
	4th	1.000
	5th	0.750
	6th	0.653
	Rev.	5.027

WEIGHT CAPACITIES, kg (lbs.)	
GAWR - Front Axle	6,350 (14,000)
GAWR - Rear Axle	10,430 (23,000)

AXLE / SUSPENSION	
Front Axle	Reversed Elliot, "I" beam, oil lubricated
Front Spring	Taper-leaf springs with shock absorbers
Rear Axle	Full-floating, single reduction; single-speed hypoid gears
Rear Spring	Semi-elliptic leaf spring

WHY DRIVERS LOVE OUR TRUCKS	
Air conditioning	
Tilt & telescopic steering column with lock	
Steering wheel, 4 spoke, black with control switches	
Power windows and door locks with keyless entry	
Power and heated outer rearview mirrors	
Convex mirror (2)	
Driver's seat - high-back seat with air suspension & arm rest	
Passenger seat - 2-person high-back bench seat	
Cruise control	
1000W/120V engine block heater	
Rear differential lock, driver control	
Air horn	
LED low & high beam	
Air Suspension, Hendrickson with dump valve	

FRAME	
Ladder Type	Straight C channel
Width, mm (in)	863 (34)
Yield Strength, kg/mm ² (psi)	87.8 (120,000)
Resisting Bending Moment, one side kgf-mm (in-lbs.)	2,317,900 (1,933,200)
Tow hook	One, front right side

CHASSIS EQUIPMENT	
Fuel Tank ltr. (US gallon)	189 (50) mounted under cab, driver's side
Bumper	White, 3-piece
Fuel pre-filter	Heated fuel water separator
Radiator Grille	Chrome
DEF Tank ltr. (US gallon)	28 (7.0)

WHEELS / TIRES	
Wheels	22.5 x 8.25, 10-stud disc
Tires	Bridgestone 295/75R22.5
Pattern	Front: Rib, Rear: Lug

ELECTRICAL EQUIPMENT	
Batteries	Two 12V, parallel connection, 1300 CCA
Alternator	12V, 135A, brushless
Starter kW (hp)	12V, 4.8 (6.4)
Audio System	AM/FM audio system with Bluetooth®

BRAKES	
Service Brake	Full air, dual circuit, 4-wheel drum with ABS
Parking Brake	Spring brake acting on rear wheels

OPTIONAL EQUIPMENT	
Alcoa aluminum wheels	
90-gallon aluminum fuel tank, driver's side mounted	
Multimedia audio system with Bluetooth® and Navigation	
One piece, chrome bumper	
4" front bumper extension	
Cab paint, exterior (see Dealer for available colours)	
Batteries (see Dealer for available options)	
Orange safety belts, driver & passenger	
Fender mirrors	

HINOWATCH	
No-charge, 24-hour roadside assistance for the first 3-years of ownership. HINOWATCH covers lockout service, battery jump-start and towing on warrantable repairs (max. of \$1,000 per tow).	

DIMENSIONS mm (in)	L8-187	L8-205	L8-217	L8-235	L8-253	L8-271
Wheelbase	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Cab to axle	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Overall length	7,798 (307.0)	8,255 (325.0)	8,560 (337.0)	9,474 (373.0)	9,931 (391.0)	10,389 (409.0)
Overall height	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
Overall width	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Frame height at rear axle	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Rear overhang	2,007 (79.0)	2,007 (79.0)	2,007 (79.0)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)
Turning radius - tire	7,690 (302.8)	8,350 (328.7)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius - swept	8,210 (323.2)	8,870 (349.2)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
CHASSIS WEIGHT	L8-187	L8-205	L8-217	L8-235	L8-253	L8-271
Front axle kgs (lbs.)	3,180 (7,010)	3,240 (7,145)	3,250 (7,165)	3,310 (7,295)	3,345 (7,375)	3,395 (7,485)
Rear axle kgs (lbs.)	1,940 (4,275)	1,940 (4,275)	1,950 (4,300)	1,920 (4,235)	1,915 (4,220)	1,925 (4,245)
Total weight kgs (lbs.)	5,120 (11,285)	5,180 (11,420)	5,200 (11,465)	5,230 (11,530)	5,260 (11,595)	5,320 (11,730)

NOTE :
DISCLAIMER: All specifications of the product are preliminary and subject to change or substitution prior to or during regular production. Weights provided are based on Hino J08 engine, not updated to Cummins B6.7. HINO MOTORS CANADA, LTD. reserves the right to alter specifications at any time without prior notice.

